Application No.: National Phase of PCT/CN04/001581 Docket No.: 2902246.1

First Preliminary Amendment

AMENDMENTS TO THE CLAIMS

1. (original) A button alkaline battery cell comprising an anode shell containing an anode mixture, said anode shell being interlocked with a cathode cap containing a cathode mixture, said

cathode cap having outward flange, a separator between the anode mixture and the cathode

mixture, a gasket fastened on the outward flange, wherein said gasket has a bottom and an outer

wall and is placed on the separator, wherein an open-end portion of said anode and an upper end

portion of the outer wall of the gasket are bent to the cathode cap, the upper end portion of the

outer wall of the gasket is pressed against the outer surface of the cathode cap; and wherein a

sealant layer is filled in an interspace formed between the flange of the cathode cap and the

gasket.

2. (original) The button alkaline battery cell according to claim 1, wherein said gasket

further comprises an inner wall, the bottom, the inner wall and the outer wall of the gasket form a

groove, the flange of the cathode cap is located in the groove of the gasket, and a sealant layer is

filled in the interspace between the flange of the cathode cap and the bottom, the inner wall, the

outer wall of the gasket.

3. (original) The button alkaline battery cell according to claim 2, wherein the thickness of

the inner wall of the gasket decreases along its upward direction.

4. (original) The button alkaline battery cell according to claim 1, wherein said button

alkaline battery cell further comprises a separation layer attached to the inner wall of the cathode

cap, the shape of said separation layer corresponding with the shape of the interior of the cathode

cap, wherein the bottom of the separation layer is fastened to the upper side of the bottom of the

gasket, and forms a groove with the bottom and the outer wall of the gasket; and wherein the

flange of the cathode cap is located in the groove, which is filled with a sealant layer.

2

Application No.: National Phase of PCT/CN04/001581

First Preliminary Amendment

5. (original) The button alkaline battery cell according to claim 1, wherein said flange of the cathode cap is U-shaped.

Docket No.: 2902246.1

6. (new) The button alkaline batter cell according to claim 1, wherein the sealant comprises epoxy resin.